

FORAL003



CE RoHS


TECHNICAL PARAMETERS

Dimensions:	1970mm
Housing Material:	6063 Aluminum
Finish:	Silver
Ingress Protection (IP):	IP20
Impact Protection (IK):	IK04
Luminous Flux:	8800lm UP / 2000lm DOWN
Efficacy (lm/w):	148
Power Consumption:	60W UP/20W DOWN
Color Temperature (CCT):	Tunable
Color Rendering Index (CRI):	>80
Beam Angle:	115° UP / 60° DOWN
Dimming Options:	Touching panel
Unified Glare rating (UGR):	<11
Lifespan:	L80B10 50000h
Input Voltage:	AC200~240V
Driver type:	Internal
Power Factor:	>0.9
Surge Protection:	II
Operating Temperature:	-20°C~+45 °C
Sensor Integration:	Daylight & Motion
Mounting Options:	Standing
Certifications:	CE / RoHS
Energy label:	D
SDCM:	<3

APPLICATION

The Fora L is an elegantly designed lighting solution tailored for office environments. It features a sophisticated and imaginative design that enhances any workspace. Equipped with specialized micro reflectors and anti-glare covers, it ensures a Unified Glare Rating (UGR) of less than 11, providing comfortable and soft lighting that minimizes eye strain. Ideal for illuminating up to four desks, Fora L delivers uniform lighting with independent controls for both direct and indirect light sources. The lamp also supports advanced smart functions, including motion and daylight sensors, for enhanced energy efficiency. Constructed from high-quality aluminum, steel, and PC materials, Fora L is designed for easy installation, requiring no professional assistance, making it a practical and efficient choice for modern offices. SDCM <5

LIGHT CURVE



PRODUCT DIAGRAM

