


VALIS002



**TECHNICAL PARAMETERS**


<b>Dimensions:</b>	Ø655
<b>Housing Material:</b>	6063 Aluminum
<b>Finish:</b>	Black
<b>Ingress Protection (IP):</b>	IP20
<b>Impact Protection (IK):</b>	4
<b>Luminous Flux:</b>	5900lm UP 3100lm DOWN
<b>Efficacy (lm/w):</b>	150
<b>Power Consumption:</b>	36W UP 24W DOWN
<b>Color Temperature (CCT):</b>	3000K
<b>Color Rendering Index (CRI):</b>	>80
<b>Beam Angle:</b>	115° UP 60° DOWN
<b>Dimming Options:</b>	1-10V/DALI
<b>Unified Glare rating (UGR):</b>	6
<b>Lifespan:</b>	L80B10 50000h
<b>Input Voltage:</b>	AC200~240V
<b>Driver type:</b>	Internal
<b>Power Factor:</b>	≥0.9
<b>Surge Protection:</b>	II
<b>Operating Temperature:</b>	-20°C + 45°C
<b>Sensor Integration:</b>	No
<b>Mounting Options:</b>	Pendant

<b>Certifications:</b>	CE / RoHS
<b>Energy label:</b>	D
<b>SDCM:</b>	<3

**APPLICATION**

Introducing Valis, a beautifully crafted lighting solution that combines simplicity with sophistication. Available in three sizes—655mm, 905mm, and 1205mm—it offers versatile options for any space. It features an advanced Direct/Indirect lighting system with precise beam angles and ultra-low glare (UGR<6). With high efficiency at 145 lm/w and flicker-free operation, it delivers powerful, comfortable illumination. Smart features like Motion sensors, 1-10V, DALI dimming, and CASAMBI wireless integration enhance its versatility. Built from high-quality aluminum and PC, Valis is both durable and user-friendly, with a flexible assembly structure to meet various needs. It is the perfect blend of style and cutting-edge technology for modern interiors.

**LIGHT CURVE**



**PRODUCT DIAGRAM**

