

VALIS005



CE RoHS


### TECHNICAL PARAMETERS

|                                     |                       |
|-------------------------------------|-----------------------|
| <b>Dimensions:</b>                  | Ø905                  |
| <b>Housing Material:</b>            | 6063Aluminum          |
| <b>Finish:</b>                      | White                 |
| <b>Ingress Protection (IP):</b>     | IP20                  |
| <b>Impact Protection (IK):</b>      | 4                     |
| <b>Luminous Flux:</b>               | 7400lm UP 4200lm DOWN |
| <b>Efficacy (lm/w):</b>             | 150                   |
| <b>Power Consumption:</b>           | 48W UP 32W DOWN       |
| <b>Color Temperature (CCT):</b>     | 3000K                 |
| <b>Color Rendering Index (CRI):</b> | >80                   |
| <b>Beam Angle:</b>                  | 115° UP 60° DOWN      |
| <b>Dimming Options:</b>             | 1-10V/DALI            |
| <b>Unified Glare rating (UGR):</b>  | 6                     |
| <b>Lifespan:</b>                    | L80B10 50000h         |
| <b>Input Voltage:</b>               | AC200~240V            |
| <b>Driver type:</b>                 | Internal              |
| <b>Power Factor:</b>                | ≥0.9                  |
| <b>Surge Protection:</b>            | II                    |
| <b>Operating Temperature:</b>       | -20°C + 45°C          |
| <b>Sensor Integration:</b>          | No                    |
| <b>Mounting Options:</b>            | Pendant               |
| <b>Certifications:</b>              | CE / RoHS             |
| <b>Energy label:</b>                | D                     |
| <b>SDCM:</b>                        | <3                    |

### APPLICATION

Introducing Valis, a beautifully crafted lighting solution that combines simplicity with sophistication. Available in three sizes—655mm, 905mm, and 1205mm—it offers versatile options for any space. It features an advanced Direct/Indirect lighting system with precise beam angles and ultra-low glare (UGR<6). With high efficiency at 145 lm/w and flicker-free operation, it delivers powerful, comfortable illumination. Smart features like Motion sensors, 1-10V, DALI dimming, and CASAMBI wireless integration enhance its versatility. Built from high-quality aluminum and PC, Valis is both durable and user-friendly, with a flexible assembly structure to meet various needs. It is the perfect blend of style and cutting-edge technology for modern interiors.

### LIGHT CURVE



### PRODUCT DIAGRAM

