


VALIS007



TECHNICAL PARAMETERS


Dimensions:	Ø905
Housing Material:	6063Aluminum
Finish:	White
Ingress Protection (IP):	IP20
Impact Protection (IK):	4
Luminous Flux:	7400lm UP 4200lm DOWN
Efficacy (lm/w):	150
Power Consumption:	48W UP 32W DOWN
Color Temperature (CCT):	4000K
Color Rendering Index (CRI):	>80
Beam Angle:	115° UP 60° DOWN
Dimming Options:	1-10V/DALI
Unified Glare rating (UGR):	6
Lifespan:	L80B10 50000h
Input Voltage:	AC200~240V
Driver type:	Internal
Power Factor:	≥0.9
Surge Protection:	II
Operating Temperature:	-20°C + 45°C
Sensor Integration:	No
Mounting Options:	Pendant

Certifications:	CE / RoHS
Energy label:	D
SDCM:	<3

APPLICATION

Introducing Valis, a beautifully crafted lighting solution that combines simplicity with sophistication. Available in three sizes—655mm, 905mm, and 1205mm—it offers versatile options for any space. It features an advanced Direct/Indirect lighting system with precise beam angles and ultra-low glare (UGR<6). With high efficiency at 145 lm/w and flicker-free operation, it delivers powerful, comfortable illumination. Smart features like Motion sensors, 1-10V, DALI dimming, and CASAMBI wireless integration enhance its versatility. Built from high-quality aluminum and PC, Valis is both durable and user-friendly, with a flexible assembly structure to meet various needs. It is the perfect blend of style and cutting-edge technology for modern interiors.

LIGHT CURVE



PRODUCT DIAGRAM

