

CIELXS002



PARAMETRES

Dimensions: ø110x50mm
Housing Material: Die-cast Aluminum
Finish: White
Ingress Protection (IP): 54
Impact Protection (IK): 4

Luminous Flux: 1400
Efficacy (lm/w) 140
Power Consumption: 10W
Color Temperature (CCT): 3000k
Color Rendering Index (CRI): >80
Beam Angle: 55°
Dimming Options: DALI
Unified Glare rating (UGR): <19
Lifespan: L80B10 50000h

Input Voltage: 220V
Driver type: Integrated
Power Factor: >0.90
Surge Protection: II
Operating Temperature -30°C + 45°C


Sensor Integration: No
Mounting Options: Recessed

Certifications: CE/CB/RoHS/SAA/ENEC
Energy Label: D
SDCM: <3

APPLICATION

The CIEL series downlight leverages advanced Fresnel lens technology, delivering high efficacy up to 150 lm/W. Featuring a recessed SMD2835 light source, it provides soft, glare-free lighting, with four color reflector options for versatile design. An IP54 waterproof rating ensures durability on the room-facing side. Backed by a 5-year warranty, the CIEL series offers efficient, adaptable lighting for diverse applications.

LIGHT CURVE



PRODUCT DIAGRAM

